Revision nr. 2 Dated 20/03/2019 Printed on 20/03/2019 Page n. 1/16 Replaced revision:1 (Dated: 06/11/2015)

# Safety Data Sheet

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code:

Product name Sens.ùs Inblonde Zero Yellow Deco

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Bleaching powder for hair (for cosmetic use)

1.3. Details of the supplier of the safety data sheet

Name G&P COSMETICS
Full address Via A. de Gasperi, 8
District and Country 52037 Sansepolcro (AR)

Italy

tel. +39 0575 720682 Fax +39 0575 749923

e-mail address of the competent person

responsible for the Safety Data Sheet regulatory@ilovesensus.it

1.4. Emergency telephone number

For urgent inquiries refer to Ospedale Niguarda Ca' Granda - Milano - 02/66101029

Azienda Ospedaliera S.G.Battista - Molinette - Torino - 011/6637637 Clinica Del Lavoro E Della Riabilitazione- Pavia - 0382/24444 Università Degli Studi Di Padova - Padova - 049/8275078 04 Istituto Scientifico G. Gaslini - Genova - 010/5636245 Azienza Ospedaliera Careggi - Firenze - 055/4277238

Policlinico A.Gemelli - Univ. Cattolica Del Sacro Cuore - Roma - 06/3054343

Centro Antiveleni - Università La Sapienza - Roma - 06/49970698

Centro Antiveleni Azienda Ospedaliera A. Cardarelli - Napoli - 081/7472870

#### **SECTION 2. Hazards identification**

# 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

H272	May intensify fire; oxidiser.
H302	Harmful if swallowed.
H318	Causes serious eye damage.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H334	May cause allergy or asthma symptoms or breathing
	H302 H318 H315 H335

Revision nr. 2 Dated 20/03/2019 Printed on 20/03/2019 Page n. 2/16 Replaced revision:1 (Dated: 06/11/2015)

Skin sensitization, category 1

H317

difficulties if inhaled. May cause an allergic skin reaction.

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

#### Hazard pictograms:









Signal words:

Danger

#### Hazard statements:

H272 May intensify fire; oxidiser.
H302 Harmful if swallowed.
H318 Causes serious eye damage.
H315 Causes skin irritation.
H335 May cause respiratory irritation.

**H334** May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**H317** May cause an allergic skin reaction.

#### Precautionary statements:

**P210** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust / fume / gas / mist / vapours / spray.
P220 Keep away from clothing and other combustible materials.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing

P310 Immediately call a POISON CENTER / doctor / . . .

P304+P340 IF INHALED: remove person to fresh air and keep comfortable for breathing.

P370+P378 In case of fire: use . . . to extinguish.

**P280** Wear protective gloves/ protective clothing / eye protection / face protection.

Contains: SODIUM SILICATE

DISODIUM METASILICATE

DIPOTASSIUM PEROXODISULPHATE AMMONIUM PEROXYDISULPHATE

#### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

### **SECTION 3. Composition/information on ingredients**

Revision nr 2 Dated 20/03/2019 Printed on 20/03/2019 Replaced revision:1 (Dated: 06/11/2015)

#### 3.2. Mixtures

Contains:

Identification x = Conc. % Classification 1272/2008 (CLP)

**DIPOTASSIUM PEROXODISULPHATE** 

Ox. Sol. 3 H272, Acute Tox. 4 H302, Eye Irrit. 2 H319, Skin Irrit. 2 H315, CAS 7727-21-1  $25 \le x < 50$ 

STOT SE 3 H335, Resp. Sens. 1 H334, Skin Sens. 1 H317 EC 231-781-8

INDEX 016-061-00-1

Reg. no. 01-2119495676-19-0000

**SODIUM SILICATE** 

CAS 1344-09-8  $20 \le x < 25$ Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335

EC 215-687-4 INDEX -

Reg. no. 01-2119448725-31-0011

**AMMONIUM** 

**PEROXYDISULPHATE** 

Ox. Sol. 3 H272, Acute Tox. 4 H302, Eye Irrit. 2 H319, Skin Irrit. 2 H315,  $10 \le x < 20$ CAS 7727-54-0

STOT SE 3 H335, Resp. Sens. 1 H334, Skin Sens. 1 H317

EC 231-786-5

INDEX 016-060-00-6

Reg. no. 01-2119495973-19-0000

**DISODIUM METASILICATE** 

CAS 6834-92-0  $3 \le x < 5$ Met. Corr. 1 H290, Skin Corr. 1B H314, Eye Dam. 1 H318, STOT SE 3 H335

EC 229-912-9

INDEX 014-010-00-8

Reg. no. 01-2119449811-37-xxxx

**MINERAL OIL** 

CAS 8042-47-5 Asp. Tox. 1 H304  $1 \le x < 5$ 

EC 232-455-8 INDEX -

Reg. no. 01-2119487078-27-0000

The full wording of hazard (H) phrases is given in section 16 of the sheet.

#### **SECTION 4. First aid measures**

#### 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

Revision nr 2 Dated 20/03/2019 Printed on 20/03/2019

Replaced revision:1 (Dated: 06/11/2015)

# **G&P COSMETICS S.R.L.** Sens.ùs Inblonde Zero Yellow Deco

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

#### **SECTION 5. Firefighting measures**

#### 5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

#### 5.2. Special hazards arising from the substance or mixture

#### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products. The product is combustible and, when the powder is released into the air in sufficient concentrations and in the presence of a source of ignition, it can create explosive mixtures with air. Fires may start or get worse by leakage of the solid product from the container, when it reaches high temperatures or through contact with sources of ignition.

#### 5.3. Advice for firefighters

#### **GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

#### **SECTION 6. Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

If there are no contraindications, spray powder with water to prevent the formation of dust.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product and place it in containers for recovery or disposal. If there are no contraindications, use jets of water to eliminate product

Make sure the leakage site is well aired. Evaluate the compatibility of the container to be used, by checking section 10. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

# **G&P COSMETICS S.R.L.**

Revision nr. 2 Dated 20/03/2019 Printed on 20/03/2019 Page n. 5/16

Replaced revision:1 (Dated: 06/11/2015)

# Sens.ùs Inblonde Zero Yellow Deco

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## **SECTION 7. Handling and storage**

#### 7.1. Precautions for safe handling

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

Store in cool (below 30 °C) and dry areas. Avoid contamination and avoid the presence of reducing agents like lotions and permanent waves. Discard any unused mixture with developer or bleaching lotions, since the container may break. AVOID humid organic material as paper towel, wood, clothes, etc. which could induce spontaneous combustion. Protect from heat and sunlight; store in places far from rain and humidity; never store outdoors. Store separately from other dangerous and incompatible substances.

## 7.3. Specific end use(s)

Information not available

#### **SECTION 8. Exposure controls/personal protection**

#### 8.1. Control parameters

Regulatory References:

ESP España INSHT - Lími TI V-ACGIH ACGIH 2018

INSHT - Límites de exposición profesional para agentes químicos en España 2017

#### **DIPOTASSIUM PEROXODISULPHATE**

DIFOTASSION PEROXODISOLPHATE			
Predicted no-effect concentration - PNEC			
Normal value in fresh water	0,0763	mg/l	
Normal value in marine water	0,011	mg/l	
Normal value for fresh water sediment	0,275	mg/kg	_
Normal value for marine water sediment	0,0396	mg/kg	
Normal value for water, intermittent release	0,763	mg/l	
Normal value of STP microorganisms	3,6	mg/l	
Normal value for the terrestrial compartment	0,015	mg/kg	

Health -	Derived	no-effect	level -	DNEL	/ DMEL

Health - Delived no-ene	CLIEVEL - DIVLE / D	IVILL							
Effects on				Effects on					
	consumers				workers				
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic	Acute local	Acute	Chronic local	Chronic	

# G&P COSMETICS S.R.L.

Revision nr. 2 Dated 20/03/2019 Printed on 20/03/2019 Page n. 6/16 Replaced revision:1 (Dated: 06/11/2015)

# Sens.ùs Inblonde Zero Yellow Deco

				systemic		systemic		systemic
Oral		30 mg/kg bw/d		9,1 mg/kg bw/d				•
nhalation	295 mg/m3	295 mg/m3	1,03 mg/m3	1,03 mg/m3		590 mg/m3	2,06 mg/m3	2,06 mg/m3
Skin	1,124 mg/cm2	200 mg/kg bw/d	0,051 mg/cm2	9,1 mg/kg bw/d	2,248 mg/cm2	400 mg/kg bw/d	0,102 mg/cm2	18.2 mg/kg bw/d
SODIUM SILICATE								
Predicted no-effect concentral	tion - PNEC							
Normal value in fresh water				7,5	mg	ı/l		
Normal value for marine water	rsediment			1	mg	j/l		
Normal value for water, interm	ittent release			7,5	mg	<b>1/</b> I		
Normal value of STP microorg	janisms			348	mg	ı/l		
Health - Derived no-effec	et level - DNEL / DN Effects on consumers	MEL			Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	0,80 mg/kg bw/d		Systemin		Systemic
nhalation			VND	1,38 mg/m3			VND	5,61 mg/m3
Skin			VND	0,8 mg/kg bw/d			VND	1,59 mg/kg bw/d
AMMONIUM PEROXYDIS Threshold Limit Value	SULPHATE							
Гуре	Country	TWA/8h		STEL/15min				
		mg/m3	ppm	mg/m3	ppm			
VLA	ESP	0,1						
TLV-ACGIH		0,1						
Predicted no-effect concentrate	tion - PNEC							
Normal value in fresh water				0,0763	mg	<b>1/</b> I		
Normal value in marine water				0,011	mg	ı/l		
Normal value for fresh water s	ediment			0,275	mg	ı/kg		
Normal value for marine water	r sediment			0,0396	mg	ı/kg		
Normal value for water, interm	ittent release			0,763	mg	ı/l		
Normal value of STP microorg	ganisms			3,6	mg	ı/I		
Normal value for the terrestria	I compartment			0,015	mg	ı/kg		
Health - Derived no-effec	et level - DNEL / DN Effects on consumers	MEL			Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic	Acute local	Acute	Chronic local	Chronic
Oral		30 mg/kg bw/d		systemic 9,1 mg/kg bw/d		systemi C		systemic
nhalation	295 mg/m3	295 mg/m3	1,03 mg/m3	1,03 mg/m3		590 mg/m3	2,06 mg/m3	2,06 mg/m3
Skin	1,124 mg/cm2	200 mg/kg bw/d	0,051 mg/cm2	9,1 mg/kg bw/d	2,248 mg/cm2	400 mg/kg bw/d	0,102 mg/cm2	18,2 mg/kg bw/d
DISODIUM METASILICA	ΓE							

Revision nr. 2 Dated 20/03/2019 Printed on 20/03/2019 Page n. 7/16 Replaced revision:1 (Dated: 06/11/2015)

# **G&P COSMETICS S.R.L.**

# Sens.ùs Inblonde Zero Yellow Deco

Route of exposure Oral	Acute local	Acute systemic	Chronic local	Chronic systemic 0,74 mg/kg bw/d	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation				1,55 mg/m3		6,22		6,22 mg/m3
Skin				0,74 mg/kg bw/d				1,49 mg/kg bw/d
MINERAL OIL Threshold Limit Value								
Туре	Country	TWA/8h		STEL/15min				
		mg/m3	ppm	mg/m3	ppm			
TLV-ACGIH		5						
Health - Derived no-effect le	vel - DNEL / DM Effects on consumers	IEL			Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	40 mg/kg bw/d		.,		.,
Inhalation			VND	35 mg/m3			VND	160 mg/m3
Skin			VND	220 mg/kg bw/d			VND	220 mg/kg bw/d

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

 $\label{eq:ND} VND = hazard\ identified\ but\ no\ DNEL/PNEC\ available\ ;\ NEA = no\ exposure\ expected\ ;\ NPI = no\ hazard\ identified.$ 

During the risk assessment process, it is essential to take into consideration the ACGIH occupational exposure levels for inert particulate not otherwise classified (PNOC respirable fraction: 3 mg/m3; PNOC inhalable fraction: 10 mg/m3). For values above these limits, use a P type filter, whose class (1, 2 or 3) must be chosen according to the outcome of risk assessment.

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

#### HAND PROTECTION

In the case of prolonged contact with the product, protect the hands with penetration-resistant work gloves (see standard EN 374). Work glove material must be chosen according to the use process and the products that may form. Latex gloves may cause sensitivity reactions.

#### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

#### **EYE PROTECTION**

Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental

Revision nr. 2 Dated 20/03/2019 Printed on 20/03/2019 Page n. 8/16 Replaced revision:1 (Dated: 06/11/2015)

# G&P COSMETICS S.R.L. Sens.ùs Inblonde Zero Yellow Deco

absorption.

#### RESPIRATORY PROTECTION

Use a type P filtering facemask, whose class (1, 2 or 3) and effective need, must be defined according to the outcome of risk assessment (see standard EN 149).

#### **ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## **SECTION 9. Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Appearance powder Colour violet Odour characteristic Odour threshold Not available рΗ 9.7-10.7 Melting point / freezing point Not available Initial boiling point Not available Not available Boiling range Not available Flash point Evaporation rate Not available Not available Flammability (solid, gas) Not available Lower inflammability limit Upper inflammability limit Not available Lower explosive limit Not available Upper explosive limit Not available Not available Vapour pressure Vapour density Not available Relative density Not available partially soluble Solubility Partition coefficient: n-octanol/water Not available Auto-ignition temperature Not available Decomposition temperature Not available Not available Viscosity Explosive properties Not available Oxidising properties Not available

#### 9.2. Other information

Information not available

## **SECTION 10. Stability and reactivity**

#### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

#### DISODIUM METASILICATE

The aqueous solutions act as: strong bases.

Revision nr. 2 Dated 20/03/2019 Printed on 20/03/2019 Page n. 9/16 Replaced revision:1 (Dated: 06/11/2015)

1	0.2.	Che	emical	stak	oility

The product is stable in normal conditions of use and storage.

#### 10.3. Possibility of hazardous reactions

The powders are potentially explosive when mixed with air.

DISODIUM METASILICATE

May react dangerously with: fluorine, lithium.

#### 10.4. Conditions to avoid

Avoid environmental dust build-up.

#### 10.5. Incompatible materials

**DISODIUM METASILICATE** 

The aqueous solution is incompatible with: acids,organic anhydrides,acrilates,alcohols,aldehydes,alkyl oxides,cresoles,caprolactam,epichlorohydrin,ethylene dichloride,glycols,isocyanates,ketones,nitrates,phenoles,vinyl acetate.

#### 10.6. Hazardous decomposition products

Information not available

## **SECTION 11. Toxicological information**

#### 11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

**ACUTE TOXICITY** 

Revision nr. 2 Dated 20/03/2019 Printed on 20/03/2019 Page n. 10/16 Replaced revision:1 (Dated: 06/11/2015)

LC50 (Inhalation) of the mixture: Not classified (no significant component) LD50 (Oral) of the mixture: 1186,97 mg/kg LD50 (Dermal) of the mixture: Not classified (no significant component)

#### SODIUM SILICATE

LD50 (Oral) 3400 mg/ kg (rat)

LD50 (Dermal) > 5000 mg/kg (rat)

LC50 (Inhalation) > 2,06 g/m3 (rat)

#### DIPOTASSIUM PEROXODISULPHATE

LD50 (Oral) 1130 mg/kg (ratto)

LD50 (Dermal) > 10000 mg/kg (coniglio)

LC50 (Inhalation) > 42,9 mg/l (ratto)

#### **DISODIUM METASILICATE**

LD50 (Oral) 1152 mg/kg bw (Ratto)

LD50 (Dermal) > 5000 mg/kg bw (Ratto)

LC50 (Inhalation) > 2,06 g/m3 (Ratto)

#### AMMONIUM PEROXYDISULPHATE

LD50 (Oral) 272 mg/kg Rat

LD50 (Dermal) > 2000 mg/kg Rat

LC50 (Inhalation) > 5,1 mg/l/4h Rat

#### SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Revision nr. 2 Dated 20/03/2019 Printed on 20/03/2019 Page n. 11/16

Replaced revision:1 (Dated: 06/11/2015)

# **G&P COSMETICS S.R.L.** Sens.ùs Inblonde Zero Yellow Deco

Causes serious eye damage

#### **RESPIRATORY OR SKIN SENSITISATION**

Sensitising for the skin Sensitising for the respiratory system

#### **GERM CELL MUTAGENICITY**

Does not meet the classification criteria for this hazard class

#### **CARCINOGENICITY**

Does not meet the classification criteria for this hazard class

#### REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

#### **STOT - SINGLE EXPOSURE**

May cause respiratory irritation

#### STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

### **ASPIRATION HAZARD**

Does not meet the classification criteria for this hazard class

### **SECTION 12. Ecological information**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

#### 12.1. Toxicity

MINERAL OIL

EC50 - for Crustacea 100 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants 100 mg/l/72h Pseudokirchneriella subcapitata

SODIUM SILICATE

LC50 - for Fish 1108 mg/l/96h (Brachydanio rerio) 1700 mg/l/48h (Daphnia magna) EC50 - for Crustacea

DIPOTASSIUM PEROXODISULPHATE

Revision nr. 2 Dated 20/03/2019 Printed on 20/03/2019 Page n. 12/16 Replaced revision:1 (Dated: 06/11/2015)

LC50 - for Fish 107,6 mg/l/96h Scophthalmus maximus

EC50 - for Crustacea 120 mg/l/48h (daphnia)
EC50 - for Algae / Aquatic Plants 320 mg/l/72h Phaeodactylum

DISODIUM METASILICATE

LC50 - for Fish 1108 mg/l/96h (Brachydanio rerio)
EC50 - for Crustacea 1700 mg/l/48h (Daphnia magna)

EC50 - for Algae / Aquatic Plants 207 mg/l/72h (Schenedesmus subspicatus)

AMMONIUM PEROXYDISULPHATE

LC50 - for Fish 107,6 mg/l/96h Scophthalmus maximus

EC50 - for Crustacea
 EC50 - for Algae / Aquatic Plants
 EC10 for Algae / Aquatic Plants
 320 mg/l/72h Phaeodactylum
 EC10 for Algae / Aquatic Plants
 36 mg/l/72h Pseudomonas putida

12.2. Persistence and degradability

DIPOTASSIUM PEROXODISULPHATE

Rapidly degradable

DISODIUM METASILICATE

Solubility in water 210000 mg/l

Degradability: information not available

AMMONIUM PEROXYDISULPHATE

Solubility in water > 10000 mg/l

Degradability: information not available

12.3. Bioaccumulative potential

Information not available

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

Revision nr. 2 Dated 20/03/2019 Printed on 20/03/2019 Page n. 13/16 Replaced revision:1 (Dated: 06/11/2015)

### **SECTION 13. Disposal considerations**

#### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

### **SECTION 14. Transport information**

#### 14.1. UN number

ADR / RID, IMDG,

1479

IATA:

#### 14.2. UN proper shipping name

ADR / RID: OXIDIZING SOLID, N.A.S. (potassium persulfate, ammonium persulfate).

IMDG: OXIDIZING SOLID, N.O.S. IATA: OXIDIZING SOLID, N.O.S.

#### 14.3. Transport hazard class(es)

ADR / RID: Class: 5.1 Label: 5.1

IMDG: Class: 5.1 Label: 5.1

IATA: Class: 5.1 Label: 5.1



#### 14.4. Packing group

ADR / RID, IMDG, III

IATA:

#### 14.5. Environmental hazards

ADR / RID: NO IMDG: NO IATA: NO

#### 14.6. Special precautions for user

Revision nr. 2 Dated 20/03/2019 Printed on 20/03/2019 Page n. 14/16 Replaced revision:1 (Dated: 06/11/2015)

# **G&P COSMETICS S.R.L.** Sens.ùs Inblonde Zero Yellow Deco

ADR / RID: HIN - Kemler: 50 Limited Tunnel Quantities: 5 restriction

kg

code: (E)

Packaging

Special Provision: -

Pass.:

EMS: F-A, S-Q

Limited

Quantities: 5

Kg

Cargo: Maximum quantity: 100

instructions: 563 Packaging

Maximum quantity: 25

instructions: 559

Special Instructions:

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

IMDG:

IATA:

## **SECTION 15. Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: P8

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Contained substance

Point 65 **AMMONIUM** 

PEROXYDISULPHA TE Reg. no.: 01-2119495973-19-0000

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

# **G&P COSMETICS S.R.L.**

Sens.ùs Inblonde Zero Yellow Deco

Revision nr. 2 Dated 20/03/2019 Printed on 20/03/2019 Page n. 15/16 Replaced revision:1 (Dated: 06/11/2015)

None

#### Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

#### 15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

### **SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Ox. Sol. 3 Oxidising solid, category 3

Met. Corr. 1 Substance or mixture corrosive to metals, category 1

Acute Tox. 4 Acute toxicity, category 4

Asp. Tox. 1 Aspiration hazard, category 1

Skin Corr. 1B Skin corrosion, category 1B

Eye Dam. 1 Serious eye damage, category 1

Eye Irrit. 2 Eye irritation, category 2
Skin Irrit. 2 Skin irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

Resp. Sens. 1Respiratory sensitization, category 1Skin Sens. 1Skin sensitization, category 1H272May intensify fire; oxidiser.H290May be corrosive to metals.H302Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.
H319 Causes serious eye irritation.

H315 Causes skin irritation.

H335 May cause respiratory irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals

#### Revision nr 2 Dated 20/03/2019 Printed on 20/03/2019

Replaced revision:1 (Dated: 06/11/2015)

# **G&P COSMETICS S.R.L.**

# Sens.ùs Inblonde Zero Yellow Deco

- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

#### **GENERAL BIBLIOGRAPHY**

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- The Merck Index. 10th Edition
   Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control: therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.