

**M3K all shades except 4.4 - 6.4 - 7.34 - 6.04 - 7.04 - 5.14 - 6.14 - 5.3 - 7.4
- 7.44 - 6.34 - 6.43 - 6.44 - 6.4 - 6.3 - 5.4 - 6.45 - 5.45 - 11.3ss - 11.7ss -
11.13ss - 11.0ss - 11.1ss - 11.2ss**

Safety data sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **G&P5**
Product name: **M3K all shades except 4.4 - 6.4 - 7.34 - 6.04 - 7.04 - 5.14 - 6.14 - 5.3 - 7.4 - 7.44 - 6.34 - 6.43 - 6.44 - 6.4 - 6.3 - 5.4 - 6.45 - 5.45 - 11.3ss - 11.7ss - 11.13ss - 11.0ss - 11.1ss - 11.2ss**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **Cream hair colour**

1.3. Details of the supplier of the safety data sheet

Name: **G&P COSMETICS SRL**
Full address: **Via Alcide De Gasperi,8**
District and Country: **52037 Sansepolcro (AR)
ITALIA**
Tel. **0575-720682**
Fax **0575-749923**

e-mail address of the competent person

responsible for the Safety Data Sheet: **regulatory@ilovesensus.it**
Product distribution by: **G&P COSMETICS SRL**

1.4. Emergency telephone number

For urgent inquiries refer to: **02 66101029 Centro Antiveleni di Milano**

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

2.1.1. Regulation 1272/2008 (CLP) and following amendments and adjustments.

Hazard classification and indication:

Acute Tox. 4	H302
Skin Corr. 1B	H314
Eye Dam. 1	H318
STOT SE 3	H335
Skin Sens. 1A	H317
Aquatic Chronic 2	H411

2.1.2. 67/548/EEC and 1999/45/EC Directives and following amendments and adjustments.

Danger Symbols:

Xi-N

R phrases:

31-41-43-51/53

**M3K all shades except 4.4 - 6.4 - 7.34 - 6.04 - 7.04 - 5.14 - 6.14 - 5.3 - 7.4
- 7.44 - 6.34 - 6.43 - 6.44 - 6.4 - 6.3 - 5.4 - 6.45 - 5.45 - 11.3ss - 11.7ss -
11.13ss - 11.0ss - 11.1ss - 11.2ss**

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Danger

Hazard statements:

H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H335 May cause respiratory irritation.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.
EUH031 Contact with acids liberates toxic gas.
EUH208 Contains:
 4-AMINO-M-CRESOL, PHENYL METHYL PYRAZOLONE, RESORCINOL

May produce an allergic reaction.

Precautionary statements:

P264 Wash . . . thoroughly after handling.
P273 Avoid release to the environment.
P280 Wear protective gloves / protective clothing / eye protection / face protection.
P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor / physician if you feel unwell.
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Contains: ETHANOLAMINE
 LAURETH-3
 1-HYDROXYETHYL 4,5-DIAMINO PYRAZOLE SULFATE
 p-fenilendiammina
 p-AMINO-o-CRESOLO
 N,N-BIS(2-HYDROXYETHYL)-P-PHENYLENEDIAMINE SULFATE
 2,4-DIAMINOPHENOXYETHANOL HCL
 TOLUENE 2,5-DIAMINE SULFATE

2.3. Other hazards.

Information not available.

SECTION 3. Composition/information on ingredients.

**M3K all shades except 4.4 - 6.4 - 7.34 - 6.04 - 7.04 - 5.14 - 6.14 - 5.3 - 7.4
- 7.44 - 6.34 - 6.43 - 6.44 - 6.4 - 6.3 - 5.4 - 6.45 - 5.45 - 11.3ss - 11.7ss -
11.13ss - 11.0ss - 11.1ss - 11.2ss**

3.1. Substances.

Information not relevant.

3.2. Mixtures.

Contains:

Identification.	Conc. %.	Classification 67/548/EEC.	Classification 1272/2008 (CLP).
TOLUENE 2,5-DIAMINE SULFATE			
CAS. 615-50-9	0,001 - 6	T R25, Xn R20/21, Xi R43, N R50/53	Acute Tox. 3 H301, Acute Tox. 4 H312, Acute Tox. 4 H332, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410
EC. 210-431-8			
INDEX. 612-030-00-7			
ETHANOLAMINE			
CAS. 141-43-5	4,5 - 5	C R34, Xn R20/21/22	Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Corr. 1A H314, STOT SE 3 H335, Aquatic Chronic 3 H412
EC. 205-483-3			
INDEX. 603-030-00-8			
Reg. no. 01-2119486455-28-0001			
LAURETH-3			
CAS. 68439-50-9	4 - 4,5	Xi R41, N R50	Eye Dam. 1 H318, Aquatic Acute 1 H400 M=1
EC. -			
INDEX. -			
AMMONIA			
CAS. 1336-21-6	2,5 - 3	C R34, N R50, Note B	Skin Corr. 1B H314, STOT SE 3 H335, Aquatic Acute 1 H400 M=1, Note B
EC. 215-647-6			
INDEX. 007-001-01-2			
Cocamidopropyl Betaine			
CAS. 61789-40-0	2 - 2,5	Xi R41	Eye Dam. 1 H318
EC. -			
INDEX. -			
p-AMINO-o-CRESOLO			
CAS. 2835-95-2	0,001 - 2	Xi R36/37/38, Xi R43, N R50/53	Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410
EC. 220-618-6			
INDEX. -			
1-HYDROXYETHYL 4,5-DIAMINO PYRAZOLE SULFATE			
CAS. 155601-30-2	0,001 - 2	Xi R41, Xi R43, N R51/53	Eye Dam. 1 H318, Skin Sens. 1 H317, Aquatic Chronic 2 H411
EC. 429-300-3			
INDEX. -			
N,N-BIS(2-HYDROXYETHYL)-P-PHENYLENEDIAMINE SULFATE			
CAS. 54381-16-7	0,001 - 2	Xn R22, Xi R36/38, Xi R43	Acute Tox. 3 H301, Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1 H317
EC. 259-134-5			
INDEX. -			

G&P COSMETICS SRL

Revision nr. 1

Dated 1/9/2015

Printed on 01/09/2015

**M3K all shades except 4.4 - 6.4 - 7.34 - 6.04 - 7.04 - 5.14 - 6.14 - 5.3 - 7.4
- 7.44 - 6.34 - 6.43 - 6.44 - 6.4 - 6.3 - 5.4 - 6.45 - 5.45 - 11.3ss - 11.7ss -
11.13ss - 11.0ss - 11.1ss - 11.2ss**

Page n. 4/17

1-NAPHTHOL

CAS. 90-15-3 0,001 - 2 Xn R21/22, Xi R37/38, Xi R41 Acute Tox. 4 H302, Acute Tox. 4 H312, Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335

EC. 201-969-4

INDEX. 604-029-00-5

p-fenilendiammina

CAS. 106-50-3 0,001 - 1,5 T R23/24/25, Xi R36, Xi R43, N R50/53 Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3 H331, Eye Irrit. 2 H319, Skin Sens. 1 H317, Aquatic Chronic 1 H410

EC. -

INDEX. -

M-AMINOPHENOL

CAS. 591-27-5 0,001 - 1,5 Xn R20/22, N R51/53 Acute Tox. 4 H302, Acute Tox. 4 H332, Aquatic Chronic 2 H411

EC. 209-711-2

INDEX. 612-127-00-4

2,4-DIAMINOPHENOXYETHANOL HCL

CAS. 66422-95-5 0,001 - 1,5 Xn R22, Xi R36/37, Xi R43 Acute Tox. 4 H302, Eye Irrit. 2 H319, STOT SE 3 H335, Skin Sens. 1 H317

EC. -

INDEX. -

p-AMINOPHENOL

CAS. 123-30-8 0,001 - 1 Muta. Cat. 3 R68, Xn R20/22, N R50/53 Muta. 2 H341, Acute Tox. 4 H302, Acute Tox. 4 H332, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410

EC. 204-616-2

INDEX. 612-128-00-X

2-AMINO-3-HYDROXYPYRIDINE

CAS. 16867-03-1 0,001 - 1 T R25, Xi R36/37/38 Acute Tox. 3 H301, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335

EC. 240-886-8

INDEX. -

RESORCINOL

CAS. 108-46-3 0,001 - 0,7 Xn R22, Xi R36/38, N R50 STOT SE 1 H370, Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1

EC. 203-585-2

INDEX. -

Reg. no. 01-2119480136-40-

BASIC YELLOW 87

CAS. 68259-00-7 0,001 - 0,6 Xn R22, N R51/53 Acute Tox. 4 H302, Aquatic Chronic 2 H411

EC. 269-503-2

INDEX. -

4-AMINO-M-CRESOL

CAS. 2835-99-6 0,001 - 0,35 Xn R22, Xi R36/37/38, Xi R43, N R50/53 Acute Tox. 4 H302, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410

EC. 220-621-2

INDEX. -

SODIUM DITHIONITE

CAS. 7775-14-6 0,15 - 0,2 R31, O R 7, Xn R22 Self-heat. 1 H251, Acute Tox. 4 H302, EUH031

EC. 231-890-0

INDEX. 016-028-00-1

2-METHYLRESORCINOL

**M3K all shades except 4.4 - 6.4 - 7.34 - 6.04 - 7.04 - 5.14 - 6.14 - 5.3 - 7.4
- 7.44 - 6.34 - 6.43 - 6.44 - 6.4 - 6.3 - 5.4 - 6.45 - 5.45 - 11.3ss - 11.7ss -
11.13ss - 11.0ss - 11.1ss - 11.2ss**

In the case of fire, use jets of water to cool the containers to prevent the risk of explosions (product decomposition and excess pressure) and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Remove all containers containing the product from the fire, if it is safe to do so.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.**6.1. Personal precautions, protective equipment and emergency procedures.**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.**7.1. Precautions for safe handling.**

Ensure that there is an adequate earthing system for the equipment and personnel. In order to avoid the risk of fires and explosions, never use compressed air when handling. Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Avoid leakage of the product into the environment. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Keep the product in clearly labelled containers. Keep containers well sealed. Store in a ventilated and dry place, far away from sources of ignition. Avoid violent blows. Avoid overheating. Avoid contact with water.

7.3. Specific end use(s).

Information not available.

SECTION 8. Exposure controls/personal protection.**8.1. Control parameters.**

M3K all shades except 4.4 - 6.4 - 7.34 - 6.04 - 7.04 - 5.14 - 6.14 - 5.3 - 7.4 - 7.44 - 6.34 - 6.43 - 6.44 - 6.4 - 6.3 - 5.4 - 6.45 - 5.45 - 11.3ss - 11.7ss - 11.13ss - 11.0ss - 11.1ss - 11.2ss

Regulatory References:

United Kingdom	EH40/2005 Workplace exposure limits. Containing the list of workplace exposure limits for use with the Control of Substances Hazardous to Health Regulations (as amended).
Éire	Code of Practice Chemical Agent Regulations 2011.
OEL EU	Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC.
TLV-ACGIH	ACGIH 2012

TOLUENE 2,5-DIAMINE SULFATE

Predicted no-effect concentration - PNEC.

Normal value in fresh water	0,0126	mg/L
Normal value in marine water	0,00126	mg/L
Normal value for fresh water sediment	0,0112	mg/Kg
Normal value for marine water sediment	0,00112	mg/Kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers.			Effects on workers			
	Acute local	Acute systemic	Chronic local	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation.			VND		0,49 mg/m3		
Skin.			VND		0,10 mg/Kg/d		

ETHANOLAMINE**Threshold Limit Value.**

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
TLV-ACGIH		2,5	1	7,6	3

Predicted no-effect concentration - PNEC.

Normal value for the terrestrial compartment	0,035	mg/kg
Normal value in fresh water	0,085	mg/l
Normal value in marine water	0,0085	mg/l
Normal value for fresh water sediment	0,425	mg/kg
Normal value for marine water sediment	0,0425	mg/kg
Normal value of STP microorganisms	100	mg/l

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers.			Effects on workers			
	Acute local	Acute systemic	Chronic local	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral.			VND		3.75 mg/kg		
Inhalation.			2 mg/m3		2 mg/m3	3.3 mg/m3	VND
Skin.			VND		0.24 mg/kg	VND	1 mg/kg

AMMONIA**Threshold Limit Value.**

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
TLV-ACGIH		17	25	24	35

p-fenilendiammina**Threshold Limit Value.**

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm

**M3K all shades except 4.4 - 6.4 - 7.34 - 6.04 - 7.04 - 5.14 - 6.14 - 5.3 - 7.4
- 7.44 - 6.34 - 6.43 - 6.44 - 6.4 - 6.3 - 5.4 - 6.45 - 5.45 - 11.3ss - 11.7ss -
11.13ss - 11.0ss - 11.1ss - 11.2ss**

TLV-ACGIH

1

SKIN

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

If the product may or must come into contact or react with acids, suitable technical and/or organisational measures should be taken to prevent the development of toxic and/or inflammable gases.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance	cream
Colour	white to beige
Odour	characteristic
Odour threshold.	Not available.
pH.	9,3 - 11,4

**M3K all shades except 4.4 - 6.4 - 7.34 - 6.04 - 7.04 - 5.14 - 6.14 - 5.3 - 7.4
- 7.44 - 6.34 - 6.43 - 6.44 - 6.4 - 6.3 - 5.4 - 6.45 - 5.45 - 11.3ss - 11.7ss -
11.13ss - 11.0ss - 11.1ss - 11.2ss**

Melting point / freezing point.	Not available.
Initial boiling point.	Not available.
Boiling range.	Not available.
Flash point.	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Relative density.	0.960 - 0.970
Solubility	Not available.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	Not available.
Decomposition temperature.	Not available.
Viscosity	30000 - 40000 cps
Explosive properties	Not available.
Oxidising properties	Not available.

9.2. Other information.

Information not available.

SECTION 10. Stability and reactivity.**10.1. Reactivity.**

There are no particular risks of reaction with other substances in normal conditions of use.

AMMONIA: corrodes aluminium, iron, zinc, copper and their alloys.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

AMMONIA: risk of explosion on contact with strong acids and iodine. Can react dangerously with strong bases .

10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials.

AMMONIA: silver, lead, zinc and their salts; hydrochloric acid, nitric acid, oleum, halogens, acrolein, nitromethane and acrylic acid.

10.6. Hazardous decomposition products.

AMMONIA: nitric oxides.

**M3K all shades except 4.4 - 6.4 - 7.34 - 6.04 - 7.04 - 5.14 - 6.14 - 5.3 - 7.4
- 7.44 - 6.34 - 6.43 - 6.44 - 6.4 - 6.3 - 5.4 - 6.45 - 5.45 - 11.3ss - 11.7ss -
11.13ss - 11.0ss - 11.1ss - 11.2ss**

SECTION 11. Toxicological information.

11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

Acute effects: ingestion of this product is harmful. Even small amounts of product may cause serious health problems (stomach pain, nausea, sickness, diarrhoea).

This product is corrosive and causes serious burns and vesicles on the skin, which can arise even after exposure. Burns are very stinging and painful. Upon contact with eyes, it may cause serious harm, such as cornea opacity, iris lesions, irreversible eye coloration. Possible vapours are caustic for the respiratory system and may cause pulmonary edema, whose symptoms sometimes arise only after some hours.

Exposure symptoms may include: sting, cough, asthma, laryngitis, respiratory disorders, headache, nausea and sickness.

If swallowed, it may cause mouth, throat and oesophagus burns, sickness, diarrhoea, edema, larynx swelling and, consequently, asphyxia. Perforation of the gastro-intestinal tract is also possible.

This product may cause serious ocular lesions, cornea opacity, iris lesions, irreversible eye coloration.

Acute effects: stinging eyes. Symptoms may include: rubescence, edema, pain and lachrymation.

Vapour inhalation may moderately irritate the upper respiratory tract. Contact with skin may cause slight irritation.

Ingestion may cause health problems, including stomach pain and sting, nausea and sickness.

Acute effects: vapour inhalation may irritate the lower and upper respiratory tract and cause cough and respiratory disorders. At higher concentrations it can also cause pulmonary edema. Ingestion may cause health problems, including stomach pain and sting, nausea and sickness.

Upon contact with skin, this product causes sensitization (dermatitis). Dermatitis derives from skin irritation on the areas which repeatedly come into contact with the sensitizing agent. Cutaneous lesions may include: erythemas, edemas, papules, vesicles, pustules, scurvies, ulcerations and exudative phenomena, whose intensity varies according to illness seriousness and affected areas. Erythemas, edemas and exudative phenomena prevail during the acute phase. Scurfy skin, dryness, ulcerations and skin thickening prevail during the chronic phase.

1-HYDROXYETHYL 4,5-DIAMINO PYRAZOLE SULFATE

LD50 (Oral). > 2000 mg/kg Rat

TOLUENE 2,5-DIAMINE SULFATE

LD50 (Oral). 98 mg/kg Rat

LD50 (Dermal). 6300 mg/Kg estrapolato

LC50 (Inhalation). 1,8 mg/l/4 h estrapolato

RESORCINOL

LD50 (Oral). 510 mg/Kg rat

LD50 (Dermal). 2830 mg/Kg rat

p-fenilendiammina

LD50 (Oral). 80 mg/kg rat

p-AMINOPHENOL

LD50 (Oral). 370 mg/Kg rat

LD50 (Dermal). > 5000 mg/Kg rat

LC50 (Inhalation). > 3,4 mg/l rat

p-AMINO-o-CRESOLO

LD50 (Oral). 3600 mg/kg Rat

M-AMINOPHENOL

LD50 (Oral). 924 mg/kg Rat

N,N-BIS(2-HYDROXYETHYL)-P-PHENYLENEDIAMINE SULFATE

LD50 (Oral). 264 mg/kg Rat

**M3K all shades except 4.4 - 6.4 - 7.34 - 6.04 - 7.04 - 5.14 - 6.14 - 5.3 - 7.4
- 7.44 - 6.34 - 6.43 - 6.44 - 6.4 - 6.3 - 5.4 - 6.45 - 5.45 - 11.3ss - 11.7ss -
11.13ss - 11.0ss - 11.1ss - 11.2ss**

1-NAPHTHOL

LD50 (Oral). 2300 mg/kg Rat

2-AMINO-3-HYDROXYPYRIDINE

LD50 (Oral). 50 mg/kg Rat

2-METHYLRESORCINOL

LD50 (Oral). 200 mg/kg Rat

2,4-DIAMINOPHENOXYETHANOL HCL

LD50 (Oral). 1113 mg/kg rat

4-AMINO-M-CRESOL

LD50 (Oral). 870 mg/kg Rat

BASIC YELLOW 87

LD50 (Oral). > 500 mg/kg rat

LD50 (Dermal). > 2000 mg/kg rat

LAURETH-3

LD50 (Oral). > 5000 mg/kg Rat

PROPYLENE GLYCOL

LD50 (Oral). > 20000 mg/kg rat

LD50 (Dermal). > 2000 mg/kg rabbit

ETHANOLAMINE

LD50 (Oral). 1515 mg/kg rat

LD50 (Dermal). 2504 mg/kg rabbit

LC50 (Inhalation). > 1,3 mg/l 6 h rat

AMMONIA

LD50 (Oral). 350 mg/kg Rat

SECTION 12. Ecological information.

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it have negative effects on acquatic environment.

12.1. Toxicity.**1-HYDROXYETHYL 4,5-DIAMINO PYRAZOLE SULFATE**

LC50 - for Fish.

86,2 mg/l/96h Brachidanio rerio

EC50 - for Crustacea.

11,12 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants.

5,53 mg/l/72h Selenastrum capricornutum

TOLUENE 2,5-DIAMINE SULFATE

LC50 - for Fish.

0,36 mg/l

EC50 - for Crustacea.

0,5 mg/l

EC50 - for Algae / Aquatic Plants.

0,3 mg/l/72h

RESORCINOL

**M3K all shades except 4.4 - 6.4 - 7.34 - 6.04 - 7.04 - 5.14 - 6.14 - 5.3 - 7.4
- 7.44 - 6.34 - 6.43 - 6.44 - 6.4 - 6.3 - 5.4 - 6.45 - 5.45 - 11.3ss - 11.7ss -
11.13ss - 11.0ss - 11.1ss - 11.2ss**

LC50 - for Fish.

31,6 mg/l/96h *Leuciscus idus melanotus*

EC50 - for Crustacea.

< 1 mg/l/48h *Daphnia magna*

EC50 - for Algae / Aquatic Plants.

1,1 mg/l/72h *Chlorella pyrenoidosa*

p-fenilendiammina

LC50 - for Fish.

57 mg/l/96h pesce acqua dolce

EC50 - for Crustacea.

28 mg/l/48h *Daphnia magna*

BASIC YELLOW 87

LC50 - for Fish.

28 mg/l/96h *oncorhynchus mykiss*

EC50 - for Crustacea.

1,6 mg/l/48h *dafnia magna*

LAURETH-3

LC50 - for Fish.

> 1 mg/l/96h *Brachydanio rerio*

EC50 - for Crustacea.

> 1 mg/l/48h *Daphnia magna*

EC50 - for Algae / Aquatic Plants.

> 1 mg/l/72h *Scenedesmus subspicatus*

PROPYLENE GLYCOL

EC50 - for Crustacea.

18340 mg/l/48h *Ceriodaphnia Dubia*

LC10 for Fish.

40613 mg/l/96h *Oncorhynchus mykiss*

ETHANOLAMINE

LC50 - for Fish.

170 mg/l/96h *Carassius auratus*

EC50 - for Crustacea.

65 mg/l/48h *Daphnia magna*

EC50 - for Algae / Aquatic Plants.

2,5 mg/l/72h *Selenastrum capricornutum*

Chronic NOEC for Fish.

1,2 mg/l *Oryzias latipes*

Chronic NOEC for Crustacea.

0,85 mg/l *Daphnia magna*

AMMONIA

LC50 - for Fish.

47 mg/l/96h *Channa punctata*

EC50 - for Crustacea.

20 mg/l/48h *Daphnia magna*

12.2. Persistence and degradability.

1-HYDROXYETHYL 4,5-DIAMINO PYRAZOLE SULFATE

NOT rapidly biodegradable.

TOLUENE 2,5-DIAMINE SULFATE

NOT rapidly biodegradable.

**M3K all shades except 4.4 - 6.4 - 7.34 - 6.04 - 7.04 - 5.14 - 6.14 - 5.3 - 7.4
- 7.44 - 6.34 - 6.43 - 6.44 - 6.4 - 6.3 - 5.4 - 6.45 - 5.45 - 11.3ss - 11.7ss -
11.13ss - 11.0ss - 11.1ss - 11.2ss**

RESORCINOL
Rapidly biodegradable.

p-AMINOPHENOL
Biodegradability: Information not available.

p-AMINO-o-CRESOLO
NOT rapidly biodegradable.

N,N-BIS(2-HYDROXYETHYL)-P-PHENYLENEDIAMINE SULFATE
NOT rapidly biodegradable.

4-AMINO-M-CRESOL
NOT rapidly biodegradable.

LAURETH-3
Rapidly biodegradable.

PROPYLENE GLYCOL
Biodegradability: Information not available.

ETHANOLAMINE
Rapidly biodegradable.
12.3. Bioaccumulative potential.

Information not available.

12.4. Mobility in soil.

Information not available.

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

Information not available.

SECTION 13. Disposal considerations.**13.1. Waste treatment methods.**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Avoid littering. Do not contaminate soil, sewers and waterways.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.

**M3K all shades except 4.4 - 6.4 - 7.34 - 6.04 - 7.04 - 5.14 - 6.14 - 5.3 - 7.4
- 7.44 - 6.34 - 6.43 - 6.44 - 6.4 - 6.3 - 5.4 - 6.45 - 5.45 - 11.3ss - 11.7ss -
11.13ss - 11.0ss - 11.1ss - 11.2ss**

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

SECTION 15. Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso category. 9ii

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product Point. 3

Substances in Candidate List (Art. 59 REACH).

None.

Substances subject to authorisation (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment.

A chemical safety assessment has been performed for the following contained substances.

TOLUENE 2,5-DIAMINE SULFATE

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Muta. 2 Germ cell mutagenicity, category 2

**M3K all shades except 4.4 - 6.4 - 7.34 - 6.04 - 7.04 - 5.14 - 6.14 - 5.3 - 7.4
- 7.44 - 6.34 - 6.43 - 6.44 - 6.4 - 6.3 - 5.4 - 6.45 - 5.45 - 11.3ss - 11.7ss -
11.13ss - 11.0ss - 11.1ss - 11.2ss**

Acute Tox. 3	Acute toxicity, category 3
STOT SE 1	Specific target organ toxicity - single exposure, category 1
Acute Tox. 4	Acute toxicity, category 4
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Skin Corr. 1A	Skin corrosion, category 1A
Skin Corr. 1B	Skin corrosion, category 1B
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Skin Sens. 1	Skin sensitization, category 1
Skin Sens. 1A	Skin sensitization, category 1A
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H251	Self-heating: may catch fire.
H341	Suspected of causing genetic defects.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H370	Causes damage to organs.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH031	Contact with acids liberates toxic gas.

Text of risk (R) phrases mentioned in section 2-3 of the sheet:

R 7	MAY CAUSE FIRE.
R20/21	HARMFUL BY INHALATION AND IN CONTACT WITH SKIN.
R20/21/22	HARMFUL BY INHALATION, IN CONTACT WITH SKIN AND IF SWALLOWED.

**M3K all shades except 4.4 - 6.4 - 7.34 - 6.04 - 7.04 - 5.14 - 6.14 - 5.3 - 7.4
- 7.44 - 6.34 - 6.43 - 6.44 - 6.4 - 6.3 - 5.4 - 6.45 - 5.45 - 11.3ss - 11.7ss -
11.13ss - 11.0ss - 11.1ss - 11.2ss**

R20/22	HARMFUL BY INHALATION AND IF SWALLOWED.
R21/22	HARMFUL IN CONTACT WITH SKIN AND IF SWALLOWED.
R22	HARMFUL IF SWALLOWED.
R23/24/25	TOXIC BY INHALATION, IN CONTACT WITH SKIN AND IF SWALLOWED.
R25	TOXIC IF SWALLOWED.
R31	CONTACT WITH ACIDS LIBERATES TOXIC GAS.
R34	CAUSES BURNS.
R36	IRRITATING TO EYES.
R36/37	IRRITATING TO EYES AND RESPIRATORY SYSTEM.
R36/37/38	IRRITATING TO EYES, RESPIRATORY SYSTEM AND SKIN.
R36/38	IRRITATING TO EYES AND SKIN.
R37/38	IRRITATING TO RESPIRATORY SYSTEM AND SKIN.
R41	RISK OF SERIOUS DAMAGE TO EYES.
R43	MAY CAUSE SENSITISATION BY SKIN CONTACT.
R50	VERY TOXIC TO AQUATIC ORGANISMS.
R50/53	VERY TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.
R51/53	TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.
Muta. Cat. 3	Mutagenicity, category 3.
R68	POSSIBLE RISK OF IRREVERSIBLE EFFECTS.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

**M3K all shades except 4.4 - 6.4 - 7.34 - 6.04 - 7.04 - 5.14 - 6.14 - 5.3 - 7.4
- 7.44 - 6.34 - 6.43 - 6.44 - 6.4 - 6.3 - 5.4 - 6.45 - 5.45 - 11.3ss - 11.7ss -
11.13ss - 11.0ss - 11.1ss - 11.2ss**

1. Directive 1999/45/EC and following amendments
2. Directive 67/548/EEC and following amendments and adjustments
3. Regulation (EC) 1907/2006 (REACH) of the European Parliament
4. Regulation (EC) 1272/2008 (CLP) of the European Parliament
5. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
6. Regulation (EC) 453/2010 of the European Parliament
7. Regulation (EC) 286/2011 (II Atp. CLP) of the European Parliament
8. Regulation (EC) 618/2012 (III Atp. CLP) of the European Parliament
9. The Merck Index. - 10th Edition
10. Handling Chemical Safety
11. Niosh - Registry of Toxic Effects of Chemical Substances
12. INRS - Fiche Toxicologique (toxicological sheet)
13. Patty - Industrial Hygiene and Toxicology
14. N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
15. ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.