Revision nr. 2

Dated 31/8/2015

Printed on 01/09/2015

Page n. 1/14

M3K 4.4 - 6.4 - 7.34 - 6.04 - 7.04 - 5.14 - 6.14 - 5.3 - 7.4 - 7.44 - 6.34 - 6.43 - 6.44 - 6.4 - 6.3 - 5.4 - 6.45 - 5.45

Safety data sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: G&P3

Product name M3K 4.4 - 6.4 - 7.34 - 6.04 - 7.04 - 5.14 - 6.14 - 5.3 - 7.4 - 7.44 - 6.34 - 6.43 - 6.44 - 6.4 - 6.3 -

5.4 - 6.45 - 5.45

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Cream hair colour

1.3. Details of the supplier of the safety data sheet

Name G&P COSMETICS SRL
Full address Via Alcide De Gasperi,8
District and Country 52037 Sansepolcro (AR)

ITALIA

Tel. 0575-720682 Fax 0575-749923

e-mail address of the competent person

responsible for the Safety Data Sheet regulatory@ilovesensus.it
Product distribution by G&P COSMETICS SRL

1.4. Emergency telephone number

For urgent inquiries refer to 02 66101029 Centro Antiveleni di Milano

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

2.1.1. Regulation 1272/2008 (CLP) and following amendments and adjustments.

Hazard classification and indication:

 Muta. 2
 H341

 Acute Tox. 4
 H302

 Eye Dam. 1
 H318

 Skin Irrit. 2
 H315

 Skin Sens. 1A
 H317

 STOT SE 2
 H371

 Aquatic Chronic 2
 H411

2.1.2. 67/548/EEC and 1999/45/EC Directives and following amendments and adjustments.

Danger Symbols:

Xn

R phrases:

31-43-52/53-Muta. Cat. 3 68

Revision nr. 2

Dated 31/8/2015

Printed on 01/09/2015

Page n. 2/14

M3K 4.4 - 6.4 - 7.34 - 6.04 - 7.04 - 5.14 - 6.14 - 5.3 - 7.4 - 7.44 - 6.34 - 6.43 - 6.44 - 6.4 - 6.3 - 5.4 - 6.45 - 5.45

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:









Signal words: Danger

Hazard statements:

H341 Suspected of causing genetic defects.

H302 Harmful if swallowed.

H318 Causes serious eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H371 May cause damage to organs.

H411 Toxic to aquatic life with long lasting effects.

EUH031 Contact with acids liberates toxic gas.

EUH208 Contains:

PHENYL METHYL PYRAZOLONE, p-fenilendiammina, p-AMINO-o-CRESOLO

May produce an allergic reaction.

Precautionary statements:

P201 Obtain special instructions before use.
P273 Avoid release to the environment.

P280 Wear protective gloves / protective clothing / eye protection / face protection.
P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor / physician if you feel unwell.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

Contains: p-AMINOPHENOL

LAURETH-3 RESORCINOL

TOLUENE 2,5-DIAMINE SULFATE 2-AMINO-3-HYDROXYPYRIDINE

2.3. Other hazards.

Information not available.

SECTION 3. Composition/information on ingredients.

3.1. Substances.

Information not relevant.

Revision nr. 2

Dated 31/8/2015

Printed on 01/09/2015

Page n. 3/14

M3K 4.4 - 6.4 - 7.34 - 6.04 - 7.04 - 5.14 - 6.14 - 5.3 - 7.4 - 7.44 - 6.34 - 6.43 - 6.44 - 6.4 - 6.3 - 5.4 - 6.45 - 5.45

3.2. Mixtures.

Contains:

Identification. LAURETH-3	Conc. %.	Classification 67/548/EEC.	Classification 1272/2008 (CLP).
CAS. 68439-50-9 EC	4 - 4,5	Xi R41, N R50	Eye Dam. 1 H318, Aquatic Acute 1 H400 M=1
INDEX			
AMMONIA			
CAS. 1336-21-6	2 - 2,5	C R34, N R50, Note B	Skin Corr. 1B H314, STOT SE 3 H335, Aquatic Acute 1 H400 M=1, Note B
EC. 215-647-6			Acade 111400 M 1, Note B
INDEX. 007-001-01-2			
Cocamidopropyl Betaine			
CAS. 61789-40-0 EC	2 - 2,5	Xi R41	Eye Dam. 1 H318
INDEX			
p-AMINOPHENOL			
CAS. 123-30-8	0,001 - 2,5	Muta. Cat. 3 R68, Xn R20/22, N R50/53	Muta. 2 H341, Acute Tox. 4 H302, Acute Tox. 4 H332, Aquatic Acute 1 H400 M=1, Aquatic
EC. 204-616-2			Chronic 1 H410
INDEX. 612-128-00-X			
TOLUENE 2,5-DIAMINE SULFATE			
CAS. 615-50-9	0,001 - 2	T R25, Xn R20/21, Xi R43, N R50/53	Acute Tox. 3 H301, Acute Tox. 4 H312, Acute Tox. 4 H332, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410
EC. 210-431-8			·
INDEX. 612-030-00-7			
2-AMINO-3-HYDROXYPYRIDINE			
CAS. 16867-03-1	0,001 - 1,5	T R25, Xi R36/37/38	Acute Tox. 3 H301, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335
EC. 240-886-8			
INDEX			
RESORCINOL			
CAS. 108-46-3	0,001 - 1,5	Xn R22, Xi R36/38, N R50	STOT SE 1 H370, Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1
EC. 203-585-2			
INDEX			
Reg. no. 01-2119480136-40-			
p-AMINO-o-CRESOLO		V. D00/07/00 V. D40 V D50/50	F
CAS. 2835-95-2	0,001 - 0,8	Xi R36/37/38, Xi R43, N R50/53	Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410
EC. 220-618-6			
INDEX			
p-fenilendiammina			
CAS. 106-50-3	0,001 - 0,2	T R23/24/25, Xi R36, Xi R43, N R50/53	Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3 H331, Eye Irrit. 2 H319, Skin Sens. 1 H317, Aquatic Chronic 1 H410
EC			
INDEX			

Revision nr. 2

Dated 31/8/2015

Printed on 01/09/2015

Page n. 4/14

M3K 4.4 - 6.4 - 7.34 - 6.04 - 7.04 - 5.14 - 6.14 - 5.3 - 7.4 - 7.44 - 6.34 - 6.43 - 6.44 - 6.4 - 6.3 - 5.4 - 6.45 - 5.45

SODIUM DITHIONITE

CAS. 7775-14-6 EC. 231-890-0 0,15 - 0,2

R31, O R 7, Xn R22

Self-heat. 1 H251, Acute Tox. 4 H302, EUH031

INDEX. 016-028-00-1

SODIUM SULFITE

CAS. 7757-83-7 EC. 231-821-4 0,15 - 0,2

R31

EUH031

2-METHYLRESORCINOL

CAS. 608-25-3 EC. 210-155-8 0,001 - 0,15

T R25, Xi R36

Acute Tox. 3 H301, Eye Irrit. 2 H319

INDEX -

INDEX.

Note: Upper limit is not included into the range.

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

T+ = Very Toxic(T+), T = Toxic(T), Xn = Harmful(Xn), C = Corrosive(C), Xi = Irritant(Xi), O = Oxidizing(O), E = Explosive(E), F+ = Extremely Flammable(F+), F = Highly Flammable(F), N = Dangerous for the Environment(N)

SECTION 4. First aid measures.

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide and chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water.

Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Revision nr. 2

Dated 31/8/2015

Printed on 01/09/2015

Page n. 5/14

M3K 4.4 - 6.4 - 7.34 - 6.04 - 7.04 - 5.14 - 6.14 - 5.3 - 7.4 - 7.44 - 6.34 - 6.43 - 6.44 - 6.4 - 6.3 - 5.4 - 6.45 - 5.45

If large quantities of the product are involved in a fire, they can make it considerably worse. Do not breathe combustion products.

5.3. Advice for firefighters.

GENERAL INFORMATION

In the case of fire, use jets of water to cool the containers to prevent the risk of explosions (product decomposition and excess pressure) and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Remove all containers containing the product from the fire, if it is safe to do so.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Ensure that there is an adequate earthing system for the equipment and personnel. In order to avoid the risk of fires and explosions, never use compressed air when handling. Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Avoid leakage of the product into the environment. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Keep the product in clearly labelled containers. Keep containers well sealed. Store in a ventilated and dry place, far away from sources of ignition. Avoid violent blows. Avoid overheating. Avoid contact with water.

7.3. Specific end use(s).

Information not available.

Revision nr. 2

Dated 31/8/2015

Printed on 01/09/2015

Page n. 6/14

M3K 4.4 - 6.4 - 7.34 - 6.04 - 7.04 - 5.14 - 6.14 - 5.3 - 7.4 - 7.44 - 6.34 - 6.43 -6.44 - 6.4 - 6.3 - 5.4 - 6.45 - 5.45

SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Regulatory References:

United Kingdom EH40/2005 Workplace exposure limits. Containing the list of workplace exposure

limits for use with the Control of Substances Hazardous to Health Regulations (as

Éire Code of Practice Chemical Agent Regulations 2011.

OEL EU Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive

2000/39/EC.

ACGIH 2012 TLV-ACGIH

AMMONIA

AMMONIA					
Threshold Limit Value.					
Туре	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
TI V-ACGIH		17	25	24	35

TOLUENE 2,5-DIAMINE SULFATE

Predicted no-effect concentration - PNEC.

Normal value in fresh water	0,0126	mg/L
Normal value in marine water	0,00126	mg/L
Normal value for fresh water sediment	0,0112	mg/Kg
Normal value for marine water sediment	0.00112	ma/Ka

Health - Derived no-effect level - DNEL / DMEL

	Effects on				Effects on			
	consumers.				workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic	Acute local	Acute	Chronic local	Chronic
		•		systemic		systemic		systemic
Inhalation.			VND	0,49 mg/m3		-		-

VND Skin. 0,10 mg/Kg/d

p-fenilendiammina

Threshold Limit Value. Country TWA/8h STEL/15min Type

mg/m3 ppm mg/m3 ppm TLV-ACGIH SKIN

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Revision nr. 2

Dated 31/8/2015

Printed on 01/09/2015

Page n. 7/14

M3K 4.4 - 6.4 - 7.34 - 6.04 - 7.04 - 5.14 - 6.14 - 5.3 - 7.4 - 7.44 - 6.34 - 6.43 - 6.44 - 6.4 - 6.3 - 5.4 - 6.45 - 5.45

If the product may or must come into contact or react with acids, suitable technical and/or organisational measures should be taken to prevent the development of toxic and/or inflammable gases.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance cream white to beige Colour Odour characteristic Odour threshold. Not available. 9,3 - 11,4 Melting point / freezing point. Not available. Initial boiling point. Not available. Boiling range. Not available. Flash point. Not available. Evaporation rate Not available Flammability (solid, gas) Not available. Lower inflammability limit. Not available. Upper inflammability limit. Not available Lower explosive limit. Not available. Upper explosive limit. Not available. Vapour pressure. Not available. Not available. Vapour density Relative density. 0.960 - 0.970 Not available. Solubility Partition coefficient: n-octanol/water Not available Auto-ignition temperature. Not available. Decomposition temperature. Not available. Viscosity 30000 - 40000 cps Explosive properties Not available. Oxidising properties Not available.

9.2. Other information.

Revision nr. 2

Dated 31/8/2015

Printed on 01/09/2015

Page n. 8/14

M3K 4.4 - 6.4 - 7.34 - 6.04 - 7.04 - 5.14 - 6.14 - 5.3 - 7.4 - 7.44 - 6.34 - 6.43 - 6.44 - 6.4 - 6.3 - 5.4 - 6.45 - 5.45

Information not available.

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

AMMONIA: corrodes aluminium, iron, zinc, copper and their alloys.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

AMMONIA: risk of explosion on contact with strong acids and iodine. Can react dangerously with strong bases .

10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials.

AMMONIA: silver, lead, zinc and their salts; hydrochloric acid, nitric acid, oleum, halogens, acrolein, nitromethane and acrylic acid.

10.6. Hazardous decomposition products.

AMMONIA: nitric oxides.

SECTION 11. Toxicological information.

11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

This product must be handled carefully because of its possible mutagenic effects. Anyway, currently available data are insufficient to definitively prove hereditary gene alterations.

Acute effects: ingestion of this product is harmful. Even small amounts of product may cause serious health problems (stomach pain, nausea, sickness, diarrhoea).

This product may cause serious ocular lesions, cornea opacity, iris lesions, irreversible eye coloration.

Acute effects: contact with skin may cause: irritation, erythema, edema, dryness and chapped skin. Vapour inhalation may slightly irritate the upper respiratory trait. Ingestion may cause health disorders, including stomach pain and sting, nausea and sickness.

Upon contact with skin, this product causes sensitization (dermatitis). Dermatitis derives from skin irritation on the areas which repeatedly come into contact with the sensitizing agent. Cutaneous lesions may include: erythemas, edemas, papules, vesicles, pustules, scurvies, ulcerations and exudative phenomena, whose intensity varies according to illness seriousness and affected areas. Erythemas, edemas and exudative phenomena prevail during the acute phase. Scurfy skin, dryness, ulcerations and skin thickening prevail during the chronic phase.

This product may cause irreversible, non-lethal damages after a single exposure by inhalation, cutaneous absorption and ingestion.

Revision nr. 2

Dated 31/8/2015

Printed on 01/09/2015

Page n. 9/14

M3K 4.4 - 6.4 - 7.34 - 6.04 - 7.04 - 5.14 - 6.14 - 5.3 - 7.4 - 7.44 - 6.34 - 6.43 - 6.44 - 6.4 - 6.3 - 5.4 - 6.45 - 5.45

TOLUENE 2,5-DIAMINE SULFATE

LD50 (Oral). 98 mg/kg Rat

LD50 (Dermal). 6300 mg/Kg estrapolato

LC50 (Inhalation). 1,8 mg/l/4 h estrapolato

RESORCINOL

LD50 (Oral). 510 mg/Kg rat

LD50 (Dermal). 2830 mg/Kg rat

p-fenilendiammina

LD50 (Oral). 80 mg/kg rat

p-AMINOPHENOL

LD50 (Oral). 370 mg/Kg rat

LD50 (Dermal). > 5000 mg/Kg rat

LC50 (Inhalation). > 3,4 mg/l rat

p-AMINO-o-CRESOLO

LD50 (Oral). 3600 mg/kg Rat

2-AMINO-3-HYDROXYPYRIDINE

LD50 (Oral). 50 mg/kg Rat

2-METHYLRESORCINOL

LD50 (Oral). 200 mg/kg Rat

LAURETH-3

LD50 (Oral). > 5000 mg/kg Rat

PROPYLENE GLYCOL

LD50 (Oral). > 20000 mg/kg rat

LD50 (Dermal). > 2000 mg/kg rabbit

AMMONIA

LD50 (Oral). 350 mg/kg Rat

SECTION 12. Ecological information.

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it have negative effects on acquatic environment. **12.1. Toxicity.**

TOLUENE 2,5-DIAMINE SULFATE

LC50 - for Fish.

0,36 mg/l

EC50 - for Crustacea.

0,5 mg/l

EC50 - for Algae / Aquatic Plants.

0,3 mg/l/72h

RESORCINOL

LC50 - for Fish.

31,6 mg/l/96h Leuciscus idus melanotus

EC50 - for Crustacea.

< 1 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants.

1,1 mg/l/72h Chlorella pyrenoidosa

Revision nr. 2

Dated 31/8/2015

Printed on 01/09/2015

Page n. 10/14

M3K 4.4 - 6.4 - 7.34 - 6.04 - 7.04 - 5.14 - 6.14 - 5.3 - 7.4 - 7.44 - 6.34 - 6.43 - 6.44 - 6.4 - 6.3 - 5.4 - 6.45 - 5.45

p-fenilendiammina LC50 - for Fish. 57 mg/l/96h pesce acqua dolce EC50 - for Crustacea. 28 mg/l/48h Daphnia magna

LAURETH-3 LC50 - for Fish. > 1 mg/l/96h Brachydanio rerio EC50 - for Crustacea. > 1 mg/l/48h Daphnia magna EC50 - for Algae / Aquatic Plants. > 1 mg/l/72h Scenedesmus subspicatus

PROPYLENE GLYCOL EC50 - for Crustacea. 18340 mg/l/48h Ceriodaphnia Dubia LC10 for Fish. 40613 mg/l/96h Oncorhynchus mykiss

AMMONIA LC50 - for Fish. 47 mg/l/96h Channa punctata EC50 - for Crustacea. 20 mg/l/48h Daphnia magna

12.2. Persistence and degradability.

TOLUENE 2,5-DIAMINE SULFATE NOT rapidly biodegradable.

RESORCINOL Rapidly biodegradable.

p-AMINOPHENOL Biodegradability: Information not available.

p-AMINO-o-CRESOLO NOT rapidly biodegradable.

LAURETH-3 Rapidly biodegradable.

PROPYLENE GLYCOL
Biodegradability: Information not available.
12.3. Bioaccumulative potential.

Information not available.

12.4. Mobility in soil.

Information not available.

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

Revision nr. 2

Dated 31/8/2015

Printed on 01/09/2015

Page n. 11/14

M3K 4.4 - 6.4 - 7.34 - 6.04 - 7.04 - 5.14 - 6.14 - 5.3 - 7.4 - 7.44 - 6.34 - 6.43 - 6.44 - 6.4 - 6.3 - 5.4 - 6.45 - 5.45

12.6. Other adverse effects.

Information not available.

SECTION 13. Disposal considerations.

13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Avoid littering. Do not contaminate soil, sewers and waterways.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

SECTION 15. Regulatory information.

15.1. Safety, health and environmenta	l regulations/leg	islation specific f	or the substance or mixture.
---------------------------------------	-------------------	---------------------	------------------------------

Seveso category. None.

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product.

Point. 3

Substances in Candidate List (Art. 59 REACH).

None.

Substances subject to authorisarion (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None.

Revision nr. 2

Dated 31/8/2015

Printed on 01/09/2015

Page n. 12/14

M3K 4.4 - 6.4 - 7.34 - 6.04 - 7.04 - 5.14 - 6.14 - 5.3 - 7.4 - 7.44 - 6.34 - 6.43 - 6.44 - 6.4 - 6.3 - 5.4 - 6.45 - 5.45

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment.

A chemical safety assessment has been performed for the following contained substances.

TOLUENE 2,5-DIAMINE SULFATE

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Muta. 2 Germ cell mutagenicity, category 2

Acute Tox. 3 Acute toxicity, category 3

STOT SE 1 Specific target organ toxicity - single exposure, category 1

Acute Tox. 4 Acute toxicity, category 4

STOT RE 2 Specific target organ toxicity - repeated exposure, category 2

Skin Corr. 1B Skin corrosion, category 1B

Eye Dam. 1 Serious eye damage, category 1

Eye Irrit. 2 Eye irritation, category 2
Skin Irrit. 2 Skin irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

Skin Sens. 1 Skin sensitization, category 1
Skin Sens. 1A Skin sensitization, category 1A

STOT SE 2 Specific target organ toxicity - single exposure, category 2

Aquatic Acute 1 Hazardous to the aquatic environment, acute toxicity, category 1

Aquatic Chronic 1 Hazardous to the aquatic environment, chronic toxicity, category 1

Aquatic Chronic 2 Hazardous to the aquatic environment, chronic toxicity, category 2

H251 Self-heating: may catch fire.

H341 Suspected of causing genetic defects.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H331 Toxic if inhaled.

H370 Causes damage to organs.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.
H319 Causes serious eye irritation.

H315 Causes skin irritation.

Revision nr. 2

Dated 31/8/2015

Printed on 01/09/2015

Page n. 13/14

M3K 4.4 - 6.4 - 7.34 - 6.04 - 7.04 - 5.14 - 6.14 - 5.3 - 7.4 - 7.44 - 6.34 - 6.43 - 6.44 - 6.4 - 6.3 - 5.4 - 6.45 - 5.45

H335 May cause respiratory irritation.
 H317 May cause an allergic skin reaction.
 H371 May cause damage to organs.
 H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 EUH031 Contact with acids liberates toxic gas.

Text of risk (R) phrases mentioned in section 2-3 of the sheet:

R7 MAY CAUSE FIRE.

R20/21 HARMFUL BY INHALATION AND IN CONTACT WITH SKIN.

R20/22 HARMFUL BY INHALATION AND IF SWALLOWED.

R22 HARMFUL IF SWALLOWED.

R23/24/25 TOXIC BY INHALATION, IN CONTACT WITH SKIN AND IF SWALLOWED.

R25 TOXIC IF SWALLOWED.

R31 CONTACT WITH ACIDS LIBERATES TOXIC GAS.

R34 CAUSES BURNS. R36 IRRITATING TO EYES.

R36/37/38 IRRITATING TO EYES, RESPIRATORY SYSTEM AND SKIN.

R36/38 IRRITATING TO EYES AND SKIN.
R41 RISK OF SERIOUS DAMAGE TO EYES.

R43 MAY CAUSE SENSITISATION BY SKIN CONTACT.

R50 VERY TOXIC TO AQUATIC ORGANISMS.

R50/53 VERY TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE

EFFECTS IN THE AQUATIC ENVIRONMENT.

R52/53 HARMFUL TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE

EFFECTS IN THE AQUATIC ENVIRONMENT.

Muta. Cat. 3 Mutagenicity, category 3.

R68 POSSIBLE RISK OF IRREVERSIBLE EFFECTS.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006

Revision nr. 2

Dated 31/8/2015

Printed on 01/09/2015

Page n. 14/14

M3K 4.4 - 6.4 - 7.34 - 6.04 - 7.04 - 5.14 - 6.14 - 5.3 - 7.4 - 7.44 - 6.34 - 6.43 -6.44 - 6.4 - 6.3 - 5.4 - 6.45 - 5.45

- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Directive 1999/45/EC and following amendments
- 2. Directive 67/548/EEC and following amendments and adjustments
- 3. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 4. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 5. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 6. Regulation (EC) 453/2010 of the European Parliament
- 7. Regulation (EC) 286/2011 (II Atp. CLP) of the European Parliament
- 8. Regulation (EC) 618/2012 (III Atp. CLP) of the European Parliament
- 9. The Merck Index. 10th Edition 10. Handling Chemical Safety
- 11. Niosh Registry of Toxic Effects of Chemical Substances
- 12. INRS Fiche Toxicologique (toxicological sheet)
- 13. Patty Industrial Hygiene and Toxicology
- 14. N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- 15. ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a quarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.